



6062

Overview

6062 programmable timer is suitable for many functions that require a timed operation e.g. Access Control Applications, Siren/Bell Cut Off Module, Dialer Delay, Guard Tour Supervisory Timer, etc. Some optional functions include: One Shot, Delayed Release, Delayed Operate, Delayed Pulse and Pulsar/Flasher.

Specifications

Input:

- 12VDC or 24VDC operation is selectable.

Relay:

- Selectable relay activation at the start or end of the timing cycle.
- One (1) second momentary relay activation at the end of the timing cycle (eliminates the need to use two (2) timers for this function).

Features:

- Triggers via positive DC (+) voltage, dry contact closure, or removal of contact closure.
- Quick and extremely accurate time range adjustment from 1 second to 60 minutes.

Features (cont.):

- Built-in reset feature which cancels timing cycle.
- Repeat (flasher/pulse) mode.

Visual Indicators:

- LED indicates relay is energized.

Electrical:

- Operating temperature: -20°C to 49°C ambient.

Mechanical:

- Snap Trac compatible (order Altronix model #ST3).
- Board Dimensions (L x W x H approx.):
3" (76.2mm) x 2.5" (63.5mm) x 0.75" (19.05mm).
- Product weight (approx.): 0.98 lbs. (0.44 kg).
- Shipping weight (approx.): 1.2 lbs. (0.54 kg).

Mounting Diagram

